

BT9000

System	2x tweeter + 2x midrange + 1x subwoofer + 2x passive sub-bass radiator
Functions	BT TWS / USB / microSD / AUX
Input, wired	AUX 3.5mm, stereo
Input, wireless	BT TWS STEREO
Bluetooth freq. range	2.402-2.480GHz
Bluetooth ERP	≤2.5mW / ~10m max.
Bluetooth TWS	v5.0+BR+EDR+BLE
BT profiles	A2DP1.0/AVRCP1.5/AVDTP1.0/AVCTP1.4/HFP1.5
USB file system	MP3, FAT32, max.64GB, stereo
Audio files	MP3/WAV/WMA/FLAC/APE
Pm	100 Watt
Tweeters	2 x 10 W (66mm)
Midranges	2 x 15 W (78mm)
Subwoofer	1 x 50 W (119mm)
Sub-bass	2x passive radiator
f	40 - 20.000 Hz
THD	≤0.5 %
S/N	≥80 dB
USB-C charge	5 V ^{max} / 2.8 A max.
Battery, 18650	6 x 2600mAh 12V (15600mAh)
Charging time	~7 h
Operation time	~10 h
Waterproof	IPX5 level
Ta	0 °C...+40 °C
Dimensions / Weight	507 x 223 x 188 mm / 4.7 kg